

OK E71T-1

Klassifikations svejsemetal	SFA/AWS A5.20 : E71T-1M H8 SFA/AWS A5.20 : E71T-1C H4 EN ISO 17632-A : T 42 2 P C1 1 H5 EN ISO 17632-A : T 46 2 P M21 1 H10
Godkendelser	ABS 3YSA H5 (C1) BV SA3M SA3YM H5 CE EN 13479 DNV III YMS H10 (M21) GL 3YH10S (M21) LR 3YS H5 (C1) LR 3YS H5 (C1) LR 3YS H5 (M21) PRS 3YS H5 (C1) RINA 3YS H5 (M21) RS 3YS H5 (M21)

Godkendelser er baseret på fabriksplacering. Kontakt ESAB for flere oplysninger.

Svejestrøm	DC+
Legeringstype	C Mn

Nedsmeltning Data

Diameter	Ampere	Volt	Trådfremføringshastighed	Nedsmeltning
1.0 mm	100-300 A	22-35 V	4.5-23.0 m/min	1.2-6.2 kg/h
1.2 mm	150-350 A	23-35 V	5.8-20.7 m/min	2.1-7.5 kg/h
1.4 mm	150-350 A	22-34 V	3.3-11.6 m/min	1.8-6.3 kg/h