

# Outershield® 690-H

## CLASSIFICATION

AWS A5.29	E11T1-K3M-JH4	A-Nr	10
ISO 18276-A	T 69 4 Z P M 2 H5	F-Nr	6
		9606 FM	2

## GENERAL DESCRIPTION

All position gas shielded rutile flux cored wire, for high strength steel grades like grade S690


Outstanding operator appeal

Excellent mechanical properties (CVN >70J at -40°C for 1.2 mm diameter only)

Superior product consistency with optimal alloy control

Good wire feeding

## WELDING POSITIONS (ISO/ASME)



## CURRENT TYPE / SHIELDING GAS (ISO 14175)

DC+	
M21	Mixed gas Ar+ (>15-25%) CO <sub>2</sub>
Flow rate	15-25 l/min

## APPROVALS

Shielding gas	ABS	DNV	LR	GL	RINA
M21	4YQ690H5	IVY69SH5	4Y69SH5	4Y69H5S	4Y69SH5

## CHEMICAL COMPOSITION (W%), TYPICAL, ALL WELD METAL

Shielding gas	C	Mn	Si	P	S	Ni	Mo	HDM
M21	0.06	1.5	0.2	0.015	0.010	2.0	0.3	3 ml/100 g

## MECHANICAL PROPERTIES, TYPICAL, ALL WELD METAL

	Shielding gas	Condition	Yield strength (N/mm <sup>2</sup> )	Tensile strength (N/mm <sup>2</sup> )	Elongation [%]	Impact ISO-V(J)		
						-30°C	-40°C	-46°C
Required: AWS A5.29			min. 680	760-900	min. 15	min. 27		
ISO 18276-A			min. 690	770-940	min. 17	min. 47		
Typical values	M21	AW	780	810	18	85	80	65

## PACKAGING AND AVAILABLE SIZES

Diameter (mm)	
1.2	
5 kg plastic spool S200	X
16 kg spool S300 (alu bag)	
16 kg spool B300	X

Outershield® 690-H: rev. C-EN29-15/09/21

# Outershield® 690-H

## EXAMPLES OF MATERIALS TO BE WELDED

Steel grades	Standard	Type
Fine grained steels	EN 10025 part6	S500Q to S690QL1
	API 5L	X100
	MIL-S-162164	HY100
	ASTM A514	Grade F
	ASTM A514	Grade A, B, F, H, D
ASTM A709	Grade 690 type F, grade 100W type F	

## CALCULATION DATA

Diameter (mm)	Electrical stick-out (mm)	Wire Feed Speed (cm/min)	Current (A)	Arc Voltage (V)	Deposition rate (kg/h)	kg wire/kg weldmetal
1.2	20	445	130	20-22	1.6	1.20
		700	180	23-25	2.5	1.20
		950	220	25-27	3.4	1.20
		1270	265	27-29	4.5	1.20
		1590	305	30-32	5.9	1.20

## WELDING PARAMETERS, OPTIMUM FILL PASSES IN SHIELDING GAS Ar + [>15-25]% CO<sub>2</sub>

Diameter (mm)	Welding positions				
	PA/1G	PB/2F	PC/2G	PF/3Gup	PE/4G
1.2	230-280A	230-280A	200-240A	200-240A	160-220A
	26-32V	26-32V	25-32V	25-28V	23-28V